

Impact 3336 Plus

Dotmatrix Printer



Reliable compact printer that delivers high print quality at speed reaching 540 cps.

Applications

The Impact 3336 Plus is a compact printer for general purpose and specific applications. It is ideally suited for business and industrial working environments where reliability, speed and quality are critical factors.

Outstanding performance


Designed to offer the best print techniques for a good quality output at a minimum cost. It delivers the same quality output on single sheets as well as on multiple copy forms up to 1+5 copies.

Impact 3336 Plus provides advanced paper handling to support the largest variety of papers.



Key Features

- › Print speed up to 540 cps
- › 400 million strokes per wire print head life
- › Up to 360 x 360 dpi print resolution
- › 10 million characters ribbon life
- › Up to 6 copies
- › Up to 128 KB input buffer
- › 20,000 hours MTBF
- › Advanced paper handling for trouble-free use of continuous forms
- › Standard Parallel and USB interfaces and optional serial interface
- › Integrated LAN (option)
- › Ideally designed for Continuous forms, Adhesive slip, Multicopy parts.
- › Available with built-in Arabization for full Arabic standard support



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

 www.globalis.com

Middle East, Africa
& Asia Operations

 www.alistech.ae

Technical Specifications Impact 3336 Plus

Reliable Mechanism

Impact 3336 Plus features an advanced tractor mechanism that allows flexible paper manipulation from: front in/top out, rear in/top out and from bottom in/top out. The impact 3336 Plus comes standard with a powerful 24-pin print head that functions on different types of paper using a wide range of fonts, character sets and barcodes.

Technical Specifications

Print Technology

24-pin, serial impact dot matrix

Bilingual Print speed

12 cpi	10 cpi
HSD: 540 cps	HSD: 480 cps
Draft: 435 cps	Draft: 360 cps
LQ: 145 cps	LQ: 120 cps

Character Sets

Host code sets:

ASMO-449/449+, ASMO-708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, IBM APC, XBASIC, CODAR-UFD, ICL CODAR, ICL ASMO-708, Cross Range, NCR 64/96, Data General, HP Arabic-8, HP Enhanced, Comterm 341/348/541, Integro 708 UNIX, ASMO/French, French/ASMO, User-defined

PC code sets:

ADOS-708/709/710/711/720/128 864/96, Mussaed Arabi, Arabic Windows 1256, IBM437, IBM851, IBM864

Operating Mode Support

- 8-bit Arabic with neutrals, GLCCs, & GLCCs balancing
- 7-bit Arabic with GLCCs, GLCCs balancing, & escape sequences

Arabic Fonts

Naskh Draft, Naskh NLQ

Latin Fonts

Draft, Roman, Sans Serif, OCR-A, OCR-B, etc.

Barcodes

8 types including EAN-13, Code 39, Code 128

Print Characteristics

With: Cut Sheet: 148 - 420 mm

Continuous paper: 101-406 mm

Length (cut sheet): up to 364 mm

Thickness: 0.065 to 0.52 mm

Number of Copies

Original + 5

Print Resolution 360 x 360 dpi

Number of columns 136 col.

Paper Insertion

Cut Sheet: Front in/Top out

Rear in/Top out

Continuous: Front in/Top out

Rear in/Top out

Bottom in/Top out

Interface & Connectivity

Parallel and USB interface

(standard) Optional: Serial

Optional: Integrated Ethernet

LAN 10/100 Base T

Emulation

Epson ESC P, OKI

Input Data Buffer

Up to 128 Kb

Consumables

Type: Black ribbon cartridge

Life: 10 million characters

Print Head Life

400 million strokes per wire

MTBF 20,000 hours

Physical

Dimensions (w x d x h):

623 x 395 x 173 mm

Weight: 13 kg

Operating Environment

Temperature: Operating:

5° to 35° C

Storage: -20° to 60°

Humidity: 20% to 80% (operating)

Consumptions: 15W to 75W

Acoustics: 56 dBA

Voltage: 220 v, 165 to 264 VAC

Frequency: 49.5 to 60 Hz

Warranty

Standard one-year



Let's get in touch!

info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae