

TP-803

Thermal Receipt Printer



A newly designed Thermal Receipt Printer with high reliability, high performance and cost effectiveness.

GLOBALIS TP-803 features a popular outlook classic design and offers a variety of interface options, including USB, Internet, Bluetooth, LAN and WIFI.

It includes real-time printing monitoring and a large input buffer to prevent any loss of bills, ensuring a smooth and exceptional printing experience.

Applications:

Shopping Malls, Restaurants, Stores, Warehouse, Banks, Medical Institutions, Postal Offices, etc.



Available in 3 different colors.

Compatible with:



Key Features

- > **250mm/s high-speed printing.**
- > Supports wall hanging function.
- > Printer monitoring function to prevent bill loss.
- > Equipped with a 100M Ethernet card for faster, smoother printing.
- > Re-print function after network disconnection to avoid losing bills.
- > Supports LOGO graphical download and printing.
- > 1D and 2D barcodes printing.
- > Order reminder and error alarm features.
- > Multi-language printing support.



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae

Technical Specifications TP-803

Print Parameters

Printing Method

Thermal Line

Printing with

72mm

Resolution

576 Dots/Line or 512 Dots/Line
(8dots/mm, 203dpi)

Print Speed

Max 250mm/Second

Interface

USB, Internet, Bluetooth, WIFI

(For Interface combination, please
contact your Sales Executive)

Line Spacing

3.75 mm (Line spacing can be
adjusted via command)

Line No.

FontA-48Lines/FontB-64Lines/
Simple, traditional
Chinese-24lines

Character Size

ANK character

Font A: 1.5×3.0mm (12×24 dots)

Font B: 1.1×2.1mm (9×17 dots)

Print Commands

ESC/POS

Software

Driver

Android, iOS, Linux, Windows

Barcode Character

Extended character set

PC437/Katakana/PC850/PC860/
PC863/PC865/WestEurope/
Greek/Hebrew/EastEurope/Iran/
WPC1252/PC866/PC852/PC858/
IranII/Latvian/Arabic/PT151,1251/
PC737/WPC/1257/ThaiVietnam/
PC864/PC1001/(Latvian)/(PC1001)
/(PT151,1251)/(WPC1257)/(PC864)/
(Vietnam)/(Thai)

Barcode

1D bar code: UPC-A/UPCE/
JAN13(EAN13)/JAN8(EAN8)CODE
39/ITF/CODABAR/CODE93/
CODE128

2D barcode: QR CODE

Graphics and Cutter

Graphics printing

Supports bitmap download
and print

Cutter Function

Full cut/Half cut

Paper

Type Thermal

Width 79.5±0.5mm

Diameter ≤80mm

Feed method Easy feed
(Clamshell feed)

Power

Power Adaptor

Input: AC 100V-240V,50-60Hz

Output: DC 24V/2.5A

Cash Drawer Output

DC 24V/1A

Buffer

Input Buffer 2048K bytes

NV Flash 256K bytes

Physical Characteristics

Weight 0.9KG

Dimensions 185*133*133 (MM)

Environment

Working

Temperature: 5 ~ 45°C

Humidity: 10 ~ 80%

Storage

Temperature: 10 ~ 50°C

Humidity: 10 ~ 90% (No dew)

Reliability Parameter

Print Head Life

100KM (print density≤12.5)

Cutter Life

1000,000times



Let's get in touch!

info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alitech.ae